

# **TITAN Lithium 24V 230Ah Data Sheet**

Part Number	LFP-24-230
Nominal Voltage	25.6V
Rated Capacity	230Ah (20Hr)
Capacity	5,888Wh
Achievable Capacity	Up to 250Ah
Dimensions	522mm long x 268mm wide x 218mm high (±0.5mm)
Terminal Type	M8 threaded insert (bolts included)
Case Material	ABS Plastic
Weight	≤45Kg



# Charge & Discharge

Charge Voltage	28.8V - 29.2V
Float Voltage	26.6V - 27.8V
Impedance	<10mΩ
Continuous Charge Current	200A
Continuous Discharge Current	200A

# **Temperature Windows**

Operating Temperature	Charging	-20°C to 50°C
	Discharging	-20°C to 60°C
Storage Temperature	7 days or less	-20°C to 60°C
	3 months or less	-20°C to 40°C
	4 months or more	-20°C to 25°C

	BMS Features	
<b>BMS Protection</b>		Protection Trigger
Call charge over voltage protection	Charge over voltage protection	3.65V - 3.675V
Cell charge over voltage protection	Charge over voltage protection release	3.50V - 3.525V
Dook shares averyeltage protection	Charge over voltage protection	29.20V - 29.30V
Pack charge over voltage protection	Charge over voltage protection release	28.00V - 28.20V
Call discharge under voltage protection	Discharge under voltage protection	2.525V - 2.50V
Cell discharge under voltage protection	Discharge under voltage protection release	3.00V - 3.025V
Dools dischause wader valle as a water tier.	Discharge under voltage protection	20.0V - 20.20V
Pack discharge under voltage protection	Discharge under voltage protection release	24.00V - 24.20V
	Charge over current protection	200A - 210A
Charge over current protection	Charge over current protection release	Remove charger
Di l	Primary discharge over current protection	260A - 265A
Discharge over current protection	Secondary discharge over current protection	320A - 325A
Object singuity and saling	Short circuit current protection	800A - 900A
Short circuit protection	Short circuit protection release	Remove load or charge to release
	Discharge high temperature protection	60°C - 65°C
	Discharge high temperature protection release	55°C - 60°C
	Discharge low temperature protection	-20°C25°C
	Discharge low temperature release	-10°C15°C
Temperature protection	Charge high temperature protection	60°C - 65°C
	Charge high temperature protection release	55°C - 60°C
	Charge low temperature protection	0°C - 5°C
	Charge low temperature protection release	5°C - 10°C
	Balanced start-up voltage	3.400V - 3.425V
Balancing voltage	Balanced mode	Active Balance
	Running mode	≤6mA
Power consumption	Normal sleeping	≤150uA
·	Deep sleeping	≤50uA
	Heater activation	≤3°C & on charge
Cell Heater	Heater power source	Charger
	Heater switch off	5°C - 10°C
	Accepted protocols for inverters	CAN & RS485
Communications	Batteries in parallel communication	Ethernet

#### **SECTION 1-COMPANY IDENTIFICATION**

Chemical Product Identification

Product Name: Lithium Ion Phosphate Rechargeable Battery

Common Name: Lithium Iron Phosphate (LiFePO4)
Distributed By: Groves Batteries Ltd T/A TITAN Lithium

Address: Lypiatt Street, Cheltenham, GL50 2UB, United Kingdom

Company Registration Number: 05699836

Phone Number: +44 01242 501802 Email: info@titanlithium.co.uk

# **SECTION 2 – HAZARDS IDENTIFICATION**

Emergency Overview: This product contains a chemical substance. Safety information is given for exposure to the product as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture, the below hazards exist.

#### CAS# 1333-86-4

# **Classification According to GHS**

Self-heating substances and mixtures (1) Carcinogenicity (2) Specific target organ toxicity, repeated exposure (1) (lung)

# **Label Elements Hazard Images:**





Signal Word: Danger Hazard Statements:

H251 Self-heating; may catch fire

H351 Suspected of causing cancer

H372 Causes damage to organs through prolonged or repeated exposure (lung)

Precautionary Statements:

### Prevention:

P235 Keep cool.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P260 Do not breathe dust.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

#### Response

P308+P313 If exposed seek medical attention.

P314 Seek medical attention if you feel unwell.

#### Storage:

P407 Maintain air gap between stacks or pallets.

P413 Store at temperatures not exceeding 50°C.

P420 Store separately.

P405 Store locked up.

#### Disposal:

P501 Contents require disposal at approved waste treatment plants.

#### CAS# 7440-50-8

#### Classification according to GHS

Sensitisation skin (1, 1A, 1B)

Specific target organ toxicity, single exposure (1) (digestive system) Specific target organ toxicity, single exposure;

Respiratory tract irritation (30)

### **Label Elements Hazard Images:**





Signal word: Danger Hazard Statements:

H317May cause allergic skin reaction.

H370 Causes damage to organs (digestive system).

H335 May cause respiratory irritation.

#### Prevention:

P260 Do not breathe dust, fume.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, eye protection, face protection.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271Use only outdoors or in a well-ventilated area.

#### Response:

P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Seek medical attention.

P321 Specific treatment (See additional emergency instructions). P362+P364 Take off contaminated clothing and wash it before reuse

P308+P311 IF exposed or concerned: Call a POISON CONTROL CENTRE.

P312 Call a POISON CENTRE if you feel unwell.

### Storage:

P403 +P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

# Disposal:

P501 Contents handling to approved waste treatments.

#### AS# 7429-90-5

# **Classification according to GHS**

Substances and mixtures which, in contact with water, emit flammable gases (2, 3)

Specific target organ toxicity, repeated exposure (1) (Lung) Hazardous to the aquatic environment, long-term hazard (4)

#### **Label Elements Hazard Images:**





Signal word: Danger Hazard Statements:

H261 In contact with water releases flammable gas.

H372 Causes damage to organs through prolonged or repeated. exposure (Lung).

H413 May cause long lasting harmful effects to aquatic life.

#### Prevention:

P223 Do not allow contact with water.

P231+P232 Handle and store contents under inert gas, protect with moisture.

P280 Wear protective gloves and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P273 Avoid release to the environment.

#### Response:

P302+P335+P334 IF ON SKIN: Brush off loose particles from skin and immerse in cool water.

P370+P378 In case of fire: use the appropriate media to put out the fire.

P314 Seek medical attention if you feel unwell.

#### Storage

P402+P404 Store in a dry place. Store in a closed container.

#### **Disposal**:

P501 Contents handling to approved waste treatment plants.

# **Other Hazards**

Physical and Chemical hazards: See Section 10

Human Health Hazards: See Section 11 Environmental Hazards: See Section 12

# SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

# **Chemical Characterisation: Mixture**

Chemical Composition	CAS No.	EC#	Weight (%)
Lithium iron phosphate (LiFePO4)	15365-14-7	604-917-2	20-40%
Lithium hexafluorophosphate	21324-40-3	244-334-7	10-20%
Aluminium	7429-90-5	231-072-3	10-20%
Graphite	7782-42-5	231-955-3	10-20%
Copper	7440-50-8	231-159-6	7-13%
Poly (vinyl chloride)	9002-86-2	618-338-8	1-5%

#### **SECTION 4 – FIRST AID MEASURES**



#### **Description of First Aid Measures**

General Information: No special measures required.

#### **After Eye Contact**

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

#### **After Skin Contact**

Remove contaminated clothing and shoes. Immediately wash with water and soap, rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

#### After Inhalation

Remove victim to non exposed area. Administer artificial respiration if breathing is difficult. Seek medical attention.

#### After Swallowing

Do not induce vomiting. Get medical attention.

**Personal protective equipment for first-aid responders**: No data available

Most important symptoms/effects, acute and delayed: No data available

Indication of immediate medical attention and special treatment needs: No data available

#### SECTION 5 - FIRE FIGHTING MEASURES

#### Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment, such as ABC extinguisher of the following type: a foam extinguisher, CO2, ABC dry chemical, powdered graphite, copper powder or soda (sodium carbonate) that is common to extinguish other combustible fire types.

Unsuitable extinguishing media: No data available.

# **Specific Hazards Arising from the Chemical:**

Special hazards arising from the substance or mixture Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolytes that may vent, ignite and spark when subjected to high temperature (>150°C (302°F), when damaged or abused (e.g.) mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

#### Specific protective actions for fire-fighters:

Protective equipment: wear self-contained respirator. Wear fully protective impervious suit.

# SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Protective Equipment: No data available.

**Emergency Procedures:** Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, place the spilled material into a suitable container for disposal.

Keep spilled material out of sewers, ditches and bodies of water. **Environmental Precautions:** Do not allow material to be released into the environment without proper governmental permits.

Methods and Materials for Containment and Cleaning Up:

All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### **SECTION 7 – HANDLING AND STORAGE**

# **Precautions for Safe Handling:**

Consumption of food and beverage should be avoided in work areas. Wash hands with soap and water before eating or drinking. Ground containers when transferring liquid to prevent static accumulation and discharge.

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities: Requirements to be met by storerooms and receptacles Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility Keep away from heat, avoiding long exposure to sunlight.

Further information about storage conditions

Keep container tightly sealed

Specific and use: No data available

# SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Appropriate engineering controls: The usual precautionary measures for handling chemicals should be followed. Remove all soiled and contaminated clothing immediately. Wash hands before breaks and at the end of work.

#### **Personal Protective Equipment**

Respiratory protection: Wear suitable protective mask in order to reduce the respiratory system. In case of leakage, wear chemical protective clothing, including self-contained breathing apparatus. **Hand protection:** Wear appropriate protective gloves to reduce skin contact.

**Eyes protection:** Wear safety goggles or eye protection combined with respiratory protection.

**Skin and body protection:** Working environment required, wear suitable protective clothing to minimise contact with skin. The type of protective equipment must be according to the concentration and content of certain hazardous substances in the workplace.

# SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties Colour: Black

Physical State: Prismatic Odour: Not available

Odour Threshold: Not available

pH: Not available

Melting point/freezing point: Not available

Initial boiling point and boiling range: Not available

Flash Point: Not available

Evaporation Rate: Not available

Flammability (solid, gas): Not available Explosion Limits (vol% in air): Not available Vapour Pressure, kPa at 20°C: Not available

Vapour Density: Not available

Density/Relative Density (water=1): Not available

Solubility(ies): Not available

Partition Coefficient: n-octanal/water: Not available

**Auto-iginition Temperature:** Not available **Decomposition Temperature:** Not available

Viscosity: Not available

Other Information: Not available

# **SECTION 10 – STABILITY AND REACTIVITY**

Reactivity: No data available Chemical Stability: Stable

**Possibility of Hazardous Reactions:** No data available **Conditions to Avoid:** Flames, sparks and other sources of

ignition, incompatible materials

**Incompatibilities Materials:** Oxidising agents, acid, base **Hazardous Decomposition Products:** Carbon monoxide,

carbon dioxide, lithium-oxide fumes

# SECTION 11- TOXICOLOGICAL INFORMATION

#### **Acute Toxicity:**

CAS No.	LC50/LD50	
15365-14-7	No data available	
21324-40-3	No data available	
7429-90-5	No data available	
7782-42-5	No data available	
7440-50-8	No data available	
9002-86-2	No data available	

Skin Corrosion/Irritation: No data available
Serious Eye Damage/Irritation: No data available
Respiratory or Skin Sensitisation: No data available

Germ Cell Mutagenicity: No data available

Carcinogenicity: No data available
Reproductive Toxicity: No data available

Specific Target Organ Toxicity-Single Exposure: No data

available

Specific Target Organ Toxicity-Repeated Exposure: No data

available

Aspiration Hazard: No data available

Information on the Likely Routes of Exposure: No data

available

Eve: No data available

Skin: No data available Ingestion: No data available Inhalation: No data available

# **SECTION 12 - ECOLOGICAL INFORMATION**

Ecological Toxicity: No data available

Persistence and Degradability: No data available Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

**Disposal Methods** 

Recommendation: Consult state, local or national regulations

to ensure proper disposal.

Uncleaned Packaging

Recommendation: Disposal must be made according to

official regulations.

# **SECTION 14 - TRANSPORT INFORMATION**

# **Acute Toxicity:**

LINI Nicosale en		
UN Number	UN3480	
IMDG		
ADR		
Model Regulation		
UN Proper shipping name		
IATA		
IMDG	Lithium ion battery	
ADR		
Model Regulation		
Transport Hazard Class (es)		
IATA		
IMDG	9	
ADR		
Model Regulation		
Packing group		
IATA	N/A	
IMDG		
ADR		
Model Regulation		
Packing Sign		
ATA		
IMDG		
ADR	9	
Model Regulation	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
Environmental Hazards Marine Pollutant:	No	
Special precautions for user	N/A	

#### **Transport Information:**

TITAN LiFePO4 Batteries have passed compliance tests:

UN38.3

CE

RoHS UKCA

**EMC** 

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 965 Section IA of IATA DGR for transportation, Cargo aircraft only.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 230, 348 of IMDG (37-14).

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the <<Recommendations On The Transport of Dangerous Goods-Model Regulations>>(19th).

Separate batteries to prevent short-circuiting and they should be packed in a strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames. Lithium ion cells and batteries must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.

Transport Fashion: By air, by sea, by railway, by road.

# SECTION 15 - REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IESC	DSL/NDSL	EINECS/ ELINCS/ NLP
15365-14-7	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
9002-86-2	Listed	Listed	Listed DSL	Listed

#### **SECTION 16 - OTHER INFORMATION**



Issue Department: Technical Department Modification Record: Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above names supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although., certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Other Information:

CAS: (Chemical Abstracts Service)

EC: (European Commission)

ACGIH: (American Conference of Governmental Industrial Hygienists) NIOSH: (US National Institute for Occupational Safety and

Health) OSHA: (US Occupational Safety and Health)

TLV: (Threshold Limit Value)
TWA: (Time Weighted Average)
STEL: (Short TermExposure Limit)
PEL: (Permissible Exposure Average)
REL: (Recommended Exposure Limit)

PC-STEL: (Permissible concentration-time weighted average PC-TWA: (Permissible concentration-short time exposure limit) LC50:

(Lethal concentration, 50 percent kill) LD50: Lethal dose, 50 percent kill)

IARC: (International Agency for Research on Cancer)

EC50: (Median effective concentration)

BCF: (Bio concentration Factor)

BOD: Biochemical Oxygen Demand)
NOEC: (No observed effect concentration)
NTP: (US National Toxicology Program)

RTECS: (Registry of Toxic Effects of Chemical Substances) IATA: (International Air Transport Association)

IMDG: (International Maritime Dangerous Goods)

TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)

TOC: (Total Organic Carbon)

TSCA: (Toxic Substances Control Act of USA)
DSL: 9The Domestic Substances List of Canada)
NDSL: (The Non-Domestic Substances List of Canada)